




# Arrow Flood




<b>Product Family Name:</b>	Arrow
<b>Product Family Code:</b>	ALUX-FL
<b>LED Brand:</b>	Philips Rebel ES
<b>LED Colour Temp:</b>	5500k (others available)
<b>CRI:</b>	>65
<b>Light Source Replaceable:</b>	Yes
<b>Power Supply:</b>	Meanwell - on board
<b>Optical Type:</b>	Individual optics
<b>Optical Distribution:</b>	15°, 30°, 60°, 90°, 120°, 85x135, 65x135
<b>Optical Cover/Lens:</b>	Yes
<b>Dimmable:</b>	Optional
<b>Photocell:</b>	Optional
<b>Power Cable:</b>	2m (optional to client spec)
<b>IP Rating:</b>	IP65
<b>Mounting:</b>	Stirrup bracket
<b>Aiming Angles:</b>	Yes, dial on bracket
<b>UMSUG Codes:</b>	Yes

<b>Input Voltage:</b>	230v
<b>Control Signal:</b>	(set by driver)
<b>Chassis Material:</b>	Aluminium
<b>Chassis Colour:</b>	Black
<b>Optical Cover/lens material:</b>	Glass
<b>Mechanical Accessories:</b>	n/a
<b>Weight:</b>	4kg
<b>System Power:</b>	35w
<b>Luminous flux:</b>	3048
<b>LED Luminaire efficacy:</b>	87lm/w
<b>Surge Protection</b>	Optional
<b>Working Temp:</b>	-40 to +45°C
<b>Lifetime:</b>	>50,000hrs


## Installation Configuration Schematics





Arm-mounted  
(outdoor signage board)




Canopy-mounted  
(shop facade)




Wall-mounted  
(outdoor playground)




Ceiling-mounted  
(warehouse)



Pole-mounted  
(outdoor sport field)



Pole-mounted  
(outdoor plaza)



Wall-mounted  
(tunnel lighting)

