

STREET LIGHT

STREET LIGHT M4 4300K 7000LM 68W



VESTEL
LED Aydınlatma

Product Specification



Luminous Flux	7800 lm \pm %10
Rated Power	68W
Colour Description	NW
CCT	4300K
CRI	70
Efficacy of Luminaire	115 lm/W
Beam Angle of Luminaire	Asymetrical
CBCP	-
Dimming	Opsiyon
Emergency	-
Rated Life Time	50000 hrs
Operated Temperature	-40° - +50°C
IP Rating	IP65

Electrical Specification

Number of Power Supplies	Her ürün için 1 adet
Input Voltage (Vac)	220 ~ 240Vac
Output Voltage (Vdc)	18 ~ 35Vdc
Çıkış Akımı (Idc)	1.75A \pm 5%
Frequency (Hz)	50~ 60Hz
Operating Mode	Sabit Akım
Power Factor	PF > 0,9


Mechanical Specification

Dimensions (LxWxH)	637x374.3x85.4mm
Weight	9.5kg
Packaging Type	A Box
Package Dimensions (LxWxH)	715x420x145mm
Box	BC+Dopell
Quantity in a Box	1




Photometric Specifications

Polar Diagram



Illuminance and Intensity Diagram



Luminance Table

Luminances in cd/m²

Gamma:	45°	50°	55°	60°	65°	70°	75°	80°	85°
C0:	8186	9940	12595	17046	19114	14864	7616	1474	309
C90:	5141	4666	4270	3424	2200	1353	553	156	91
C180:	8054	9486	11906	16023	18488	15884	10115	2258	470
C270:	1473	2798	1918	1364	1456	1256	693	171	71

PLC

PLC (Power Line Communications) option for smart control .