



P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED PER ECR-14-009894	08AUG2014	RS	DD
	A1	REVISED PER ECR-15-002652	03MAR2015	RS	DD

NOTES:

1. MATERIALS:
HOUSING: GLASS-FILLED THERMOPLASTIC, UL 94V-0 RATED
DIMMING CONTACTS (2 OR 4) AND LINE VOLTAGE CONTACTS (3):
COPPER ALLOY
2. FINISH:
DIMMING CONTACTS (2 OR 4): NICKEL UNDERPLATE ENTIRE
CONTACT 0.127 µm MIN THICK. GOLD PLATE CONTACT
PAD AREA (MATING FACE SIDE ONLY) 0.76 µm MIN THICK.
MATTE TIN PLATE TAB ON BOTH SIDES 0.30 µm MIN THICK.
LINE VOLTAGE CONTACTS (3): TIN PLATE.
3. LINE VOLTAGE CONDUCTORS (3):
14 AWG, 600V, 150°C RATED, COPPER 41/30 STRANDED
PER UL STYLE AWM 3321.
4. MATING INTERFACE PER ANSI C136.41-2013.
5. OPTIONAL DIMMING CONTACTS (2) SUPPLIED WITH -2 AND -4 ONLY.
6. DIMMING CONDUCTORS (2 OR 4):
18 AWG, 600V, 150°C RATED, 16/30 STRANDED,
PER UL STYLE AWM 3321.
7. LINE VOLTAGE CONDUCTORS (3):
14 AWG, 600V, 105°C RATED, COPPER 41/30 STRANDED.
PER UL STYLE AWM 1015.
8. DIMMING CONDUCTORS (2 OR 4):
18 AWG, 600V, 105°C RATED, COPPER 16/30 STRANDED.
PER UL STYLE AWM 1015.
9. LUBRICATION: GOLD PLATED CONTACT PAD SURFACES OF DIMMING
CONTACTS ARE LUBRICATED WITH A TRANSPARENT (NON-VISIBLE)
LUBRICANT TO IMPROVE DURABILITY AND PERFORMANCE. AVOID
CONTACT WITH THESE SURFACES WHICH MAY RESULT IN REMOVAL
OF LUBRICANT.



SEE SHEET 2 FOR
WIRING COLOR CODE



536.3	500.0	486.5	7 AND 8	4 5	1-2213362-4
341.1	304.8	291.3	7 AND 8	4 5	2213362-4
341.1	304.8	291.3	7 AND 8	2	2213362-3
341.1	304.8	291.3	3 AND 6	4 5	2213362-2
341.1	304.8	291.3	3 AND 6	2	2213362-1
C	A	B	WIRE STYLE	QUANTITY OF DIMMING CONTACTS	PART NO.
OVERALL LENGTH	WIRE LENGTH				

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL
-

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±
2 PLC ±0.13
3 PLC ±
4 PLC ±
ANGLES ±
FINISH

-

DWN
J. SHAFFER
26 JUN 2013

CHK
E. HOWARD
26 JUN 2013

APVD
F. HOWARD
26 JUN 2013

PRODUCT SPEC
108-32059

APPLICATION SPEC
114-32115

WEIGHT
-

Customer Drawing

TE Connectivity

NAME
RECEPTACLE ASSEMBLY,
DIMMABLE PHOTOCONTROL
-

SIZE
A2

CAGE CODE
00779

DRAWING NO
C-2213362

RESTRICTED TO
-

SCALE
1:1

SHEET
1

OF
2

REV
A1

LOC	DIST	REVISIONS					
-	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
			-	SEE SHEET 1	-	-	-

D

D

C


C

B

B

A

A



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. SHAFFER 26 JUN 2013	TE Connectivity			
DIMENSIONS:		CHK E. HOWARD 26 JUN 2013				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD E. HOWARD 26 JUN 2013	NAME RECEPTACLE ASSEMBLY, DIMMABLE PHOTOCONTROL			
mm		PRODUCT SPEC 108-32059	SIZE CAGE CODE DRAWING NO RESTRICTED TO			
0 PLC ±		APPLICATION SPEC 114-32115	A200779C-2213362			
1 PLC ±		WEIGHT -	SCALE 1:1 SHEET 2 OF 2 REV A1			
2 PLC ±0.13		Customer Drawing				
3 PLC ±						
4 PLC ±						
ANGLES ±						
FINISH						