

INDO Products – Road Specifications

RDL4




Features

- ⊙ Die cast aluminium housing
- ⊙ Post top mount or side entry mounting
- ⊙ Adjustable mounting angle
- ⊙ Efficient thermal management, providing extended LED chip lifetime
- ⊙ Optional photocell
- ⊙ Dimmable/CMS compatible

Applications

- ⊙ Roads
- ⊙ Car parks
- ⊙ Public entrances
- ⊙ Off-street areas
- ⊙ Street lighting
- ⊙ Sports facilities

INDO code explained



Stocked product code

RDL4 • 0110 • 4 • U76 • C • A • R3 • 2TGR

This product code is held in stock and has, on average, a shorter lead time.

Product codes – please choose your specifications


Model	Product code	Lamp / Power (W)	Product code	Colour temperature	Product code	Mounting	Product code
ROAD L4 Large	RDL4	90W	0090	3000K	3	Universal 76mm Post Top/Side Entry	U76
		110W	0110	4000K	4		
		120W	0120	5000K	5		
				6500K	6		
Control	Product code	Dimming	Product code	Lens type	Product code	Luminaire colour (RAL)	Product code
Mains	M	Analogue (0-10V)	A	R3 Photometry (Traffic route)	R3	Two Tone Grey	2TGR
20mm Predrilled	C	DALI	D				
NEMA	N						

Product specifications

Voltage (V)	Ambient Temperature (°C)	IP Class	Weight (KG)
120-277	-20 °C / +40 °C	IP66 (Optic)	12.9

Dimensions

Unit: mm



Photometry

