

Report Number	TRN-15313
Customer	Rod Rayner
Contact	Intalect Ltd
Product Type	IT Wireless System
Test Purpose	UMS Energy Performance Test
Sales Order Ref	20100
Works Order Number	WO-5657
Test Item Reference	TI-10237
LAB Test Method Reference	TES-20012
Test Standards	LM-79-08 and Elexon UMS Charge Code process V4.0
Lab Location Reference	UMS
Tested by	Steve Hunt
Date of Test	31/07/2015
Analysed by	Steve Hunt
Number of products tested	5

Address: LUX-TSI Ltd.,
Pencoed Technology Park,
Pencoed, Bridgend,
CF35 5AQ, UK

Telephone: +44 (0) 1656 864618

Authorised by: Gareth Jones

Email: gjones@lux-tsi.com

Signed:




I.T Wireless NA (ElephantWiFi Enterprise Tracker - Intalect)

Date: 31/07/2015

Disclaimers

This report is for the exclusive use of LUX-TSI's Customer and is provided pursuant to the agreement between LUX-TSI and its Customer. LUX-TSI's responsibility and reliability are limited to the Terms and Conditions of the agreement. LUX-TSI assumes no liability to any other party, other than the Customer in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Customer is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the LUX-TSI name or one of its marks for the sale or advertisement of the tested material, product or service must be approved in writing by LUX-TSI.

The observations and test results in this report are relevant only to the sample tested. Opinions expressed and data supplied in this report, are given in good faith, and are based on the information provided by the Customer. This report does not remove the requirement for the Customer to obtain further independent advice and in particular to instruct a notified or competent body or person to carry out further evaluation work and/or testing. Accordingly, no warranty is given, nor is any term or condition to be implied, that the product, which is the subject of this report, complies with the requirements of any EU directives.

Test Conditions

Measurements were made with an ambient temperature of 23°C +/- 2°C. Measurements were taken only after sufficient time for thermal stabilisation has been allowed.

Test Equipment

Yokogawa WT210 Power Analyzer. Kikusui PCR2000M Stable AC Power Supply
with PC control and data recording



Full data control and recording
using Labview software and full
integration of the AC Stable
Power Supply and Power
Analyser

Product Name	I.T Wireless NA (ElephantWiFi Enterprise Tracker - Intalect)
Part/Serial Number	See (Identifier) below
Type of Product	IT Wireless System
Test System Item 1	Ruckus AP
Test System Item 2	POE Brick
Test System Item 3	Nanostation #1
Test System Item 4	Nanostation #2
Ambient Temperature	23.8°C
Manufacturer	Intalect Ltd
Date of Manufacturer	2015
Thermal Management	Passive
Dimmable	Yes
Humidity	<65% RH

Test Item	Identifier	Serial Number
TI-10237A	1	371454302363
TI-10237B	2	171534005108
TI-10237C	3	171594604969
TI-10237D	4	171584304958
TI-10237E	5	241504206294



Test Conditions


	Before Test	After Test
AC Supply Voltage (V)	251.14V	250.49V
AC Supply Frequency (Hz)	50Hz	50Hz
Voltage RMS Summation of the Harmonic Components (THD)	0.09%	0.12%

The test items were stabilised according to the electrical power stability of LM79-08. Stabilization is achieved when the difference in electrical power measurement is less than 0.5%. Each test item was stabilised at 250V.

Test Results Summary

These are the summary graphs of the test results for all products tested. The raw results are on page 6 of this test report.





Power factors measured have a Leading phase angle and therefore the driver has capacitive properties.

Measurement Uncertainty

Parameter	Uncertainty
Voltage (300 V, 50/60 Hz)	$\pm 0.061 V_{rms}$
Current (200 mA, 50/60Hz)	$\pm 0.07 mA_{rms}$
Current (0.5 A, 50/60Hz)	$\pm 0.16 mA_{rms}$
Current (5 A, 50/60Hz)	$\pm 0.0016 A_{rms}$
Power (300 V, 200 mA, 50/60 Hz)	$\pm 0.032 W_{rms}$
Power (300 V, 0.5 A, 50/60 Hz)	$\pm 0.09 W_{rms}$
Power (300 V, 5 A, 50/60 Hz)	$\pm 0.0009 kW_{rms}$
Frequency (50/60 Hz)	$\pm 0.001 Hz$
Power Factor	$\pm 0.0006 PF$

Measurements of power of 0.50W or greater are made with an uncertainty of less than or equal to 2% at the 95% confidence level. Measurements of power less than 0.50W are made with an uncertainty of less than or equal to 0.01W at the 95% confidence level.

Full Test Results

Test Item	Voltage (V)	Current (mA)	Electrical Power (W)	Ambient Temp (°C)	Peak Power (VA)	Power Factor	Leading / Lagging
A	250.77	166.96	14.12	23.83	41.87	0.337	Leading
B	250.48	164.34	13.72	23.78	41.16	0.333	Leading
C	250.44	164.60	13.75	23.74	41.22	0.333	Leading
D	250.79	167.31	14.43	23.84	41.96	0.344	Leading
E	250.67	171.36	14.92	23.73	42.96	0.347	Leading
A	240.52	166.90	13.46	23.94	40.14	0.335	Leading
B	240.36	168.19	13.70	23.80	40.43	0.339	Leading
C	240.59	168.03	13.62	24.05	40.43	0.337	Leading
D	241.00	170.89	14.37	23.92	41.19	0.349	Leading
E	240.44	166.64	13.71	23.97	40.07	0.342	Leading
A	230.93	174.02	13.93	23.87	40.19	0.347	Leading
B	230.14	172.19	13.64	24.06	39.63	0.344	Leading
C	230.42	173.50	13.71	24.22	39.98	0.343	Leading
D	230.26	171.59	13.72	24.22	39.51	0.347	Leading
E	230.37	170.26	13.62	24.01	39.22	0.347	Leading
A	220.05	176.12	13.48	24.12	38.76	0.348	Leading
B	220.49	177.47	13.66	24.09	39.13	0.349	Leading
C	220.38	177.88	13.68	24.18	39.20	0.349	Leading
D	220.57	175.78	13.62	24.22	38.77	0.351	Leading
E	220.23	175.33	13.66	24.17	38.61	0.354	Leading
A	210.64	183.58	13.83	24.14	38.67	0.358	Leading
B	210.13	182.50	13.66	24.23	38.35	0.356	Leading
C	210.46	182.57	13.56	24.25	38.42	0.353	Leading
D	210.14	181.61	13.72	24.29	38.16	0.360	Leading
E	210.13	179.80	13.57	24.35	37.78	0.359	Leading


Test Item Photographs

10237-INFT-WIFINA-11536

Images of Product(s) under test. Identification of each of the products can be found on page 3 of this report




RUCKUS AP



System Setup



POE



Nanostations




POE Supply



Example of Rating Label

Appendix 1: Test item set-up



----- END OF REPORT -----