



## Specifications

Lightsource	LED 20 x Luxeon rebel TX
Isolation Class	I/II
System Power	14 - 33W
Driver Power Factor	$\cos \varphi > 0,90$ @ full load
Gross Luminous Flux	1800 - 4000 lumen
Color Temperature	2200 / 3000 / 4000 kelvin
Color Rend. Index	$Ra \geq 70$
Operating Temp.	-30° C - +35° C
Lifespan	100.000* uur / L80 @ Ta=25° C, (TM-21/LM-80)
Driver	Phillips Xitanium 40 W
Dimmer	1-10V dimmer, DALI-interface
Operation Voltage	110VAC / 230 VAC
Fixture Material	Aluminium
Glass Cover	Impact-resistant Clear Polycarbonate
Colour Material	RAL 7040 or Custom
Impact Resistance	IK10
Protection	IP66
Mounting	60 mm
Optical Technique	Asymmetric Lightwell Mirror Optics®
Certification	CE
Registration	Wereldwijde Model Registratie
Quality Control	Final Random Inspection
CE / CB / LVD	EN 60598-1, EN 60598-2-3, EN 60598-2-6, EN 62471
EMC	EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
EMF	EN 6249, WEEE 2003/108/EG, RoHS
Productie Conform	ISO 9001:2008, OHSAS 18001:2007, ISO 14001:2004
Weight	12,5 kg

## Dimensions

