



Specifications

Lightsources	LED 18 x RebelTX / Fastflex LED systeem (div. config.)
Isolation Class	I/II
System Power	8 - 36 W
Driver Power Factor	$\cos \varphi > 0,90$ @ full load
Gross Luminous Flux	1000 - 3000 lumen
Color Temperature	3000 / 4000 kelvin
Color Rend. Index	$Ra \geq 70$
Operating Temp.	-30° C - +35° C
Lifespan	100.000* hours / L80 @Ta=25° C (TM-21/LM-80)
Driver	Phillips Xitanium
Dimmer	1-10V dimmer; DALI-interface
Operation Voltage	110VAC / 230 VAC
Fixture Material	Aluminium
Glass Cover	Extra Clear Hardened Glass
Colour Material	RAL 7040 or Custom
Impact Resistance	IK08
Protection	IP65
Mounting	48 mm / 60 mm
Tilt	Horizontal: -5, 0, 5 degrees, Vertical: -5, 0, 5, 10 degrees
Optical Technique	Direct Lens System with Side Reflectors
Certification	CE
Registration	Worldwide Model Registration
Quality Control	Final Random Inspection
CE / CB / LVD	EN 60598-1, EN 60598-2-3, EN 60598-2-6, EN 62471
EMC	EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
EMF	EN 6249, WEEE 2003/108/EG, RoHS
Productie Conform	ISO 9001:2008, OHSAS 18001:2007, ISO 14001:2004
Option	Direct Current Technology
Weight	4 kg

Dimensions



