



Specifications

Lightsource	LED 48 - 60 x Rebel TX
Isolation Class	I/II
System Power	16 - 90 W
Driver Power Factor	cos phi > 0,90 @ full load
Gross Luminous Flux	1800 - 10.000 lumen
Color Temperature	3000 / 4000 kelvin
Color Rend. Index	Ra ≥ 70
Operating Temp.	-30° C - +35° C
Lifespan	100.000* hours / L80 @Ta=25° C (TM-21/LM-80)
Driver	Phillips Xitanium
Dimmer	1-10V dimmer, DALI-interface
Operation Voltage	110VAC / 230 VAC
Fixture Material	Aluminium
Glass Cover	Extra Clear Hardened Glass, Option Anti-glare
Colour Material	RAL 7040 or Custom
Impact Resistance	IK10
Protection	IP66
Mounting	60 mm / 76 mm
Tilt	Vertical: 0, 5, 10, 15 degrees, Horizontal: 0, -5, -10, -15 degrees
Optical Technique	Direct Lens System
Certification	CE
Registration	Worldwide Model Registration
Quality Control	Final Random Inspection
CE / CB / LVD	EN 60598-1, EN 60598-2-3, EN 60598-2-6, EN 62471
EMC	EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
EMF	EN 6249, WEEE 2003/108/EG, RoHS
Productie Conform	ISO 9001:2008, OHSAS 18001:2007, ISO 14001:2004
Option	Direct Current Technology
Weight	13 kg

Dimensions



