


Indico

Futuristic road and street light luminaire



Indico is a modern luminaire with a design that breathes minimalism and smart features. The luminaire is opened without tools, and automatically locks in the open position.

When opening the luminaire the power will be cut off via a 2-pole safety circuit breaker. The luminaire is made of die cast aluminum and has an impact resistant front glass, IK08.

- **IP66, Class II**
- **Energy efficient 100 lm/W**
- **Impact resistant front glass**
- **Die-cast aluminium**
- **Adjustable pole bracket, $\pm 15^\circ$**
- **Automatic night dimming**

IP66

LED

CLASS II





APPLICATIONS: Streets, parks, parking, bicycle paths and pedestrian zones.

MATERIAL: Housing in die-cast aluminium. Cooling fins on 90W and 120W versions. Tempered front glass IK08. Silicone gasket. Mounting screws in stainless steel. Powder coating in colour Pantone 8403C. Similar to RAL 7010.

INSTALLATION AND CONNECTION: Tool-less opening of housing. Turnable bracket for horizontal or vertical pole, 48-60 mm. Adjustable $\pm 15^\circ$, in steps of $2,5^\circ$. Delivered with 8 m cable on 35 W versions and 10 m cable on 60 W versions. 90 W and 120 W can be fitted with cable on request. The modular design provides long lifetime since both driver and LED module can be replaced and upgraded.



TECHNICAL DATA: Xitanium driver from Philips. 10 kV surge protection device. Samsung LED package. Asymmetric PMMA lens with light distribution type III. 220-240 V. 50-60 Hz. IP66. Class II. IK08. Windage 0,072 m². Ambient temperature -40°C to +45°C. CE.

MODELS	TYPE	SYSTEM POWER (W)	LUMINOUS FLUX (lm)	LUMINAIRE EFFICACY (lm/W)	WEIGHT (kg)	CABLE	ARTICLE NO.
	Indico, 4000K	35	3500	100	6,4	8 m	467150
	Indico, 4000K Nightdimming*	35	3500	100	6,4	8 m	467154
	Indico, 4000K	60	6000	100	6,5	10 m	467158
	Indico, 4000K Nightdimming*	60	6000	100	6,5	10 m	467162
	Indico, 4000K	90	9000	100	9	on request	467166
	Indico, 4000K Nightdimming*	90	9000	100	9	on request	467170
	Indico, 4000K	120	12000	100	9,5	on request	467174
	Indico, 4000K Nightdimming*	120	12000	100	9,5	on request	467178
	Accessory					Article number	
Indico pole bracket for 76 mm pole					467144		


*Nightdimming means that the luminaire automatically dims down during the darkest hours and reduces the energy consumption.


Nightdimming function (standard configuration).

Time	15:00-22:00	22:00-00:30	00:30-03:30	03:30-05:30	05:30-10:00
Dim level	100%	50%	30%	50%	100%




INDICO





Vertical installation




Horizontal installation



Accessory: Bracket for 76 mm pole

Features Indico

- Samsung LEDs, Ra 75
- Nightdimming
- Surge protection 10kV





All specifications subject to change. For the latest version of this product leaflet, please visit www.auralight.com/products.

2016-01-21