


SFB SMALL 8W LED

CONSTRUCTION	
CASE	EXTRUDED ALUMINIUM BASE
DIFFUSER	CLEAR OR OPAL UV STABALISED POLYCARBONATE
GASKET	SA770 LOW SMOKE LOW TOXICITY SILICONE ELASTOMER
GEAR TRAY	FORMED ALUMINIUM
FINISH	SA210E INTERPON D36 POLYESTER POWDER COATING BLACK, WHITE OR GREY (TEST REF TSL0108)

LUMINAIRE CHARACTERISTICS	
LEDs	SAMSUNG NEUTRAL WHITE
DRIVER	1 x 250mA constant current
WORKING TEMP	-25°C to 35°C
EFFECTIVE LUMENS	800lm
COLOUR TEMP	~4000k
CRI	>80
LIFETIME	+50,000hrs
IP RATING	IP65
IK RATING	IK10

Dimensions (mm)



ELECTRICAL CHARACTERISTICS	
VOLTAGE INPUT	220Vac – 240Vac rms
FREQUENCY INPUT	47 – 63Hz
TOTAL POWER CONSUMPTION	8.4W
VOLTAGE	28.5Vdc
CURRENT	250mA



Average Principal Axes Luminous Intensities (cd)

