

# PIZZA RANGE

Available in  
**LED**

Available in  
**CFL**

## A robust utility luminaire.


A range of slimline anti vandal circular fittings rated at IP65, provided in shatterproof, weather resistant and UV stabilised polycarbonate.

Provided with screw down polycarbonate diffuser in prismatic or opal, the units are also available with anti tamper screws for additional security.

Multitudes of operating options are available including: Photo-cell, High Frequency, Non Maintained and High Frequency 3hr Maintained Emergency versions. LED options are available to further reduce running and maintenance costs.

- Suitable for internal or external use.
- IP65 Rating.
- Photocell options (external use only).
- Rated for continuous use.
- Conduit entry capability.
- Anti-tamper screws available on request.
- Fused connector block available on request.
- Self test emergency version available.
- Integral microwave sensor option (internal use only).
- eMotion™ Corridor Function dimming versions available.
- LED versions available.

## Colour finish options



### LED / Lamp Types

- 16W 2D 4-Pin. 3500K. GR8 Cap.
- 28W / 38W 2D 4-Pin. 3500K. GR10 Cap.
- 2 x 9W 4-Pin G11 Cap
- LED versions.

### Material 1 Polycarbonate

- Body: Vandal resistant polycarbonate self-extinguishing fire properties in black / white / Titanium.
- Diffuser: Vandal resistant polycarbonate in opal or prismatic, with self-extinguishing fire properties.

### Material 2 Die Cast Aluminium

- Body: Die cast aluminium.
- Diffuser: Vandal resistant polycarbonate in opal or prismatic, with self-extinguishing fire properties.

### Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry.
- 3 way mains terminal block. 4 way terminal block for emergency & photocell versions.
- Screw down diffuser (with Anti Tamper screws on request).
- Photocell version - external use only.
- Microwave sensor option (internal use only).
- eMotion™ Master (Internal only) and Slave options available.


### Standards

- IP65.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.



# MINI PIZZA

Available in  
**CFL**



Size	AM
A	205mm
B	205mm
C	38mm
D	43mm

## Code Options

Options	Add suffix to code
Photocell	C
Anti Tamper Screws	T
Fused Con Block	J

Colour Finish Options	Change code
White	AM/ <b>W</b>
Titanium	AM/ <b>X</b>

Diffuser Option	Change code
Prismatic	AM/_ <b>P</b>

CFL	Mini Pizza Code	Colour Finish	Diffuser	IP Rating	Photocell
16W HF	AM/BL316U6	Black	Premium Opal	IP65	✓
2 X 9W HF	AM/BL2X9U6	Black	Premium Opal	IP65	✓

### Lamp Types

- 16W 2D 4-Pin. 3500K. GR8 Cap.
  - 2 x 9W 4-Pin G11 Cap.
  - 2 x 9W.
- PLEASE NOTE – 2700K lamps available on request.  
PLEASE NOTE – High Frequency versions are all 4-Pin.

### Material 1 Polycarbonate

- Body: Vandal resistant polycarbonate self-extinguishing fire properties in black / white / Titanium.
- Diffuser: Vandal resistant polycarbonate in opal or prismatic, with self-extinguishing fire properties.

### Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry.
- 3 way mains terminal block.
- Screw down diffuser (with Anti Tamper screws on request).
- Photocell version - external use only.



### Standards

- IP65.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.

Available in  
**CFL**



Size	AP
A	286mm
B	286mm
C	38mm
D	43mm



## Code Options

Options	Add suffix to code
3 Hour Maintained Emergency	M
Photocell	C
Anti Tamper Screws	T
Fused Con Block	J
Microwave On/Off	-9
DAYLIGHT Monitoring	-CFDP
Analogue Dim	-DA
Switch Dim	-DD
DALI / DSI Dim	-DDD

### Self Test Emergency

Prefix	APST/	Suffix	M
--------	-------	--------	---

### Colour Finish Options

White		AP/W
Titanium		AP/X

### Diffuser Option

Prismatic (Non LED Only) AP / P

## Base Option

Metal Base APM/

LED	Midi Pizza Code	Colour Finish	Diffuser	IP Rating	CRI	CCT	System Power	Delivered Lumens	Efficacy	Emergency	e-Motion Corridor	Photocell	Microwave	Dimmable	Self Test	Daylight Monitoring
LED 1800	AP/BL4LED1800	Black	Premium Opal	IP65	80	4000K	17.3W	1387lm	80lm/W	✓	✓	✓	✓	✓	✓	✓
LED 1800 250mA	AP/BL4LED1800-250	Black	Premium Opal	IP65	80	4000K	8.4W	826lm	98lm/W	✓	✓	✓	✓	✓	✓	✓
CFL	Midi Pizza Code	Colour Finish	Diffuser	IP Rating						Emergency	e-Motion Corridor	Photocell	Microwave	Dimmable	Self Test	Daylight Monitoring
28W HF	AP/BL328U6	Black		Premium Opal						✓	✓	✓	✓	✓	✓	
38W HF	AP/BL338U6	Black		Premium Opal								✓	✓	✓		

## LED / Lamp Types

- 28W / 38W 2D 4-Pin. 3500K. GR10 Cap.
- PLEASE NOTE – 2700K lamps available on request.
- PLEASE NOTE – Emergency and High Frequency versions are all 4-Pin.
- PLEASE NOTE – 38W Midi Pizza versions are High Frequency only.
- LED versions.

### Material 1 Polycarbonate

- Body: Vandal resistant polycarbonate self-extinguishing fire properties in black / white / Titanium.
- Diffuser: Vandal resistant polycarbonate in opal or prismatic, with self-extinguishing fire properties.

**Material 2 Die Cast Aluminium**

- Body: Die cast aluminium.
- Diffuser: Vandal resistant polycarbonate in opal or prismatic, with self-extinguishing fire properties.

## Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry.
- 3 way mains terminal block. 4 way terminal block for emergency & photocell versions.
- Screw down diffuser (with Anti Tamper screws on request).
- Photocell version - external use only.
- Microwave sensor option (internal use only).
- eMotion™ Master (internal only) and Slave options available.

## Standards

- IP65.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.



# MAXI PIZZA

Available in  
**LED**

Available in  
**CFL**



Size	MP
A	360mm
B	360mm
C	50mm
D	54mm



## Code Options

Options	Add suffix to code
3 Hour Maintained Emergency	M
Photocell	C
Anti Tamper Screws	T
Fused Con Block	J
Microwave On/Off	-9
Analogue Dim	-DA
Switch Dim	-DD
DALI / DSI Dim	-DDD

## Self Test Emergency

Prefix	<b>MPST/</b>	Suffix	<b>M</b>
--------	--------------	--------	----------

## Colour Finish Options

Change code
White  <b>MP/W</b>
Titanium  <b>MP/X</b>

## Diffuser Option

Change code
Prismatic (Non LED Only) <b>MP/_P</b>

## Base Option

Add to code
Metal Base <b>MPM/</b>

LED	Maxi Pizza Code	Colour Finish	Diffuser	IP Rating	CRI	CCT	System Power	Delivered Lumens	Efficacy	Emergency	e-Motion Corridor	Photocell	Microwave	Dimmable	Self Test
LED 1800	MP/BL4LED1800	Black	Premium Opal	IP65	75	4000K	16.1W	1320lm	82lm/W	✓	✓	✓	✓	✓	✓
LED 16	MP/BLLED16	Black	Premium Opal	IP65	75	4000K	24.4W	1130lm	46lm/W	✓	✓	✓	✓	✓	✓
LED 22	MP/BLLED22	Black	Premium Opal	IP65	75	4000K	36W	1716lm	47lm/W	✓	✓	✓	✓	✓	✓
LED 3000	MP/BL4LED3000	Black	Premium Opal	IP65	80	4000K	24W	2370lm	99lm/W	✓	✓	✓	✓	✓	✓

CFL	Maxi Pizza Code	Colour Finish	Diffuser	IP Rating	Emergency	e-Motion Corridor	Photocell	Microwave	Dimmable	Self Test
38W HF	MP/BL38U6	Black	Premium Opal	IP65	✓	✓	✓	✓	✓	✓

## LED / Lamp Types

- 28W / 38W 2D 4-Pin. 3500K. GR10 Cap.  
PLEASE NOTE - 2700K lamps available on request.
- PLEASE NOTE - Emergency and High Frequency versions are all 4-Pin.
- PLEASE NOTE - 38W Midi Pizza versions are High Frequency only.
- LED versions.

## Material 1 Polycarbonate

- Body: Vandal resistant polycarbonate self-extinguishing fire properties in black / white / Titanium.
- Diffuser: Vandal resistant polycarbonate in opal or prismatic, with self-extinguishing fire properties.

## Material 2 Die Cast Aluminium

- Body: Die cast aluminium.
- Diffuser: Vandal resistant polycarbonate in opal or prismatic, with self-extinguishing fire properties.

## Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry.
- 3 way mains terminal block. 4 way terminal block for emergency & photocell versions.
- Screw down diffuser (with Anti Tamper screws on request).
- Photocell version - external use only.
- Microwave sensor option (internal use only).
- eMotion™ Master (internal only) and Slave options available.

## Standards

- IP65.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.