

IGNIS Mini



Optical compartment tightness level	IP 66
Control gear compartment tightness level	IP 66
Impact resistance	IK 08
Electrical Class	I or II
Weight	4.6 kg
Windage	0.05 m²


Materials

Body/Cover/Spigot	High-pressure Die-cast Aluminum
Lens	Anti-UV Polycarbonate
Color	Black (RAL 9004) , Gray (RAL 7040)


Dimensions

Unit: mm

Post Top mode



Side Entry mode



Installation / Mounting

- Mounting: Side entry / post top, through the use of two M10 locking screws.
- 3 size spigot : 76mm / 60mm / 42mm.
- Tilt angles from -15°, -10°, -5°, 0°, +5°, +10°
- Mounting Height: 3m ~ 6m

Optical Performance

- Colour temperature: 3000K,4000K,5000K .
- Colour rendering index > 70 .
- High Quality LEDs upto 133 Lumen/Watt .
- Highly uniform light distribution.
- Photometric files are available on request,available in ies. and cie. formats.
- Different lens designs to suit different road lighting conditions.

Key points

- Simple, Slim, Compact design.
- Low cost of ownership
- Efficacy, exceeding 133 lm/W
- Flexible mounting system
- Light weight and maintenance friendly.
- 10/20LEDs ,1400 lm~ 8000 lm

Luminance Distribution

