

SD-LCS650PH300N319

LONDON CITY SMART LED LANTERN

SD-LCSLED 4K max: 32k lm 650 diameter

Smart City DALI 4000K

SD-LCS6504K243W56032k (3K and 5K also available)

ENERGY SAVING



Silvaria  **FSL**

Unit 36, Wates Way

Mitcham

Surrey

CR4 4HR

United Kingdom

Registered in England

Contact: Melinda Hart MD

www.silvariafsl.com

melinda.hart@silvariafsl.com

info@silvariafsl.com

+44 (0) 7880842588

+44 (0) 7714704189

+44 (0) 7881206818



CE

PRODUCT OVERVIEW

Part Number

SD-LCS6504K243W56032k)

Technology

Dimmable

Compatible dimmers

Mount

Housing

CRI (Ra)

Colour temperature (K)

Total luminaire wattage (W)

Rated luminous flux (lm)

Luminaire efficacy

Voltage (V)

Driver current

Driver type

Standard Colours

Distribution

IP

IK

Lamps

Manufacturer standards

Expected estimated life time (h)

Finish

Weight

Manufacturing standards

LED thermal resistance

Smart City system

SD-LCS650PH300N319/

LED

Yes

DALI

Post top/column/wall bracket side entry

High pressure die cast aluminium body

> 75

4000 (3000 and 5000 also available)

(150) - 250 W

(20,000) – max. 32,000 lm

(130) - 138 lm/W

230/240

(350) - 560 mA (up to 32,000 lm total)

Constant current

RAL Black(9005) Graphite(9011) Oyster White(1013)

Symmetric/ Asymmetric

66

08

High brightness power LEDs (NICHIA or CREE XPL)

CE marked, EN 60.598.

50,000 – 100,000/L70 – Ta 25°C

Powder coated aluminium

16,5 kg

CE marked, EN 60.598. 2-22

2.2 °C/W

Telematic/Silver Spring or LED Roadway

SD-LCS650PH300N319





LONDON CITY SMART LED LANTERN

SD-LCSLED 4K max: 32k lm 650 diameter

Smart City DALI 4000K

SD-LCS6504K243W56032k (3K and 5K also available)

PHOTOMETRY



TECHNICAL DRAWINGS

