

Report Number	SAF-21303
Customer	NET LED Ltd
Contact	Hayley Sewell
Product Type	Street Light
Test Purpose	UMS Energy Performance Test
Sales Order Ref	Q-LUX18-22510
Works Order Number	WO-11950
Test Item Reference	TI-15186
LAB Test Method Reference	TES-201012
Test Standards (if applicable)	LM-79-08 and Elexon UMS Charge Code process V4.0
Lab Location Reference	Safety Lab
Tested by	Mike Sewell
Date of Test	29/06/2018
Reviewed by	Steve Hunt
Number of products tested	5

Address: LUX-TSI Ltd.,
Pencoed Technology Park,
Pencoed, Bridgend,
CF35 5AQ, UK
Telephone: +44 (0) 1656 864618
Authorised by: Gareth Jones
Email: gjones@lux-tsi.com
Signed:




NET-15-20-06 Wyton LED streetlight 150W

Date: 29 June 2018

Disclaimers

This report is for the exclusive use of LUX-TSI's Customer and is provided pursuant to the agreement between LUX-TSI and its Customer. LUX-TSI's responsibility and reliability are limited to the Terms and Conditions of the agreement. LUX-TSI assumes no liability to any other party, other than the Customer in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Customer is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the LUX-TSI name or one of its marks for the sale or advertisement of the tested material, product or service must be approved in writing by LUX-TSI.

The observations and test results in this report are relevant only to the sample tested. Opinions expressed and data supplied in this report, are given in good faith, and are based on the information provided by the Customer. This report does not remove the requirement for the Customer to obtain further independent advice and in particular to instruct a notified or competent body or person to carry out further evaluation work and/or testing. Accordingly, no warranty is given, nor is any term or condition to be implied, that the product, which is the subject of this report, complies with the requirements of any EU directives.

Product Information		
Product	Street Light	
Product Name / Model	NET-15-20-06 Wyton LED streetlight 150W	
Part/Serial Number	See (Identifier) below	
Product Brand	NET LED Ltd	
Manufacturer	NET LED Ltd	
Category	LITE	
Rated Input Voltage	110-240V	
Rated output:	36V	
Protection Class	I	
Driver Make/Model	Leyond	LYD-MD-3030-5C12B-V2
Light Engine Make/Model	MeanWell	ELG-150-36A
Dimmable / Level Tested	Yes	100%
Product Description		
The streetlights are made of a cast metal frame housing the LED module. The driver being situated within a removable cover on the housing for the connection of the fixed wiring.		

Test Conditions			
Ambient Temperature			23 (°C)
Humidity			39 (%)
	Before Test		After Test
Voltage	249.29V		249.25V
Frequency	50Hz		50Hz
Total Harmonic Distortion	0.08%		0.07%
The test items were stabilised according to the electrical power stability of LM79-08. Stabilization is achieved when the difference in electrical power measurement is less than 0.5%. Each test item was stabilised at 250V.			
Measurements were made with an ambient temperature of 23°C +/- 2°C. Measurements were taken only after sufficient time for thermal stabilisation has been allowed.			

Product Specifications / TI Ref Numbers			
Dimension	Sample		Luminous opening
Diameter / Width	290 mm		235 mm
Length	640 mm		255 mm
Height / Depth	110 mm		5 mm
Product Test Number	Identifier		Serial Number (if applicable)
Test Item #1	15186A		N/A
Test Item #2	15186B		N/A
Test Item #3	15186C		N/A
Test Item #4	15186D		N/A
Test Item #5	15186E		N/A

Test Equipment and Description



Yokogawa WT210 Power Analyser, Kikusui PCR2000M Stable AC Power Supply with PC control and data recording




The products under test are connected to the UMS Test system which has full data control and recording using Labview software. This allows full integration of the test equipment used - Kikusui AC Stable Power Supply, Yokogawa Power Analyser, Pico Temperature Logger and a LUX-TSI distribution control panel

Test Results Summary

These are the summary graphs of the test results for all products tested. The raw results are on page 6 of this test report.





Power factors measured have a Lagging phase angle and therefore the driver has inductive properties.

Measurement Uncertainty

Parameter	Uncertainty
Voltage (300 V, 50/60 Hz)	$\pm 0.061 \text{ V}_{\text{rms}}$
Current (200 mA, 50/60Hz)	$\pm 0.07 \text{ mA}_{\text{rms}}$
Current (0.5 A, 50/60Hz)	$\pm 0.16 \text{ mA}_{\text{rms}}$
Current (5 A, 50/60Hz)	$\pm 0.0016 \text{ A}_{\text{rms}}$
Power (300 V, 200 mA, 50/60 Hz)	$\pm 0.032 \text{ W}_{\text{rms}}$
Power (300 V, 0.5 A, 50/60 Hz)	$\pm 0.09 \text{ W}_{\text{rms}}$
Power (300 V, 5 A, 50/60 Hz)	$\pm 0.0009 \text{ kW}_{\text{rms}}$
Frequency (50/60 Hz)	$\pm 0.001 \text{ Hz}$
Power Factor	$\pm 0.0006 \text{ PF}$

Measurements of power of 0.50W or greater are made with an uncertainty of less than or equal to 2% at the 95% confidence level. Measurements of power less than 0.50W are made with an uncertainty of less than or equal to 0.01W at the 95% confidence level.

Full Test Results

Test Item	Voltage (V)	Current (mA)	Electrical Power (W)	Ambient Temp (°C)	Peak Power (VA)	Power Factor	Leading / Lagging
A	249.29	596.70	146.99	26.75	148.74	0.988	Lagging
B	249.27	595.30	146.23	26.83	148.40	0.985	Lagging
C	249.27	599.70	147.39	26.87	149.48	0.986	Leading
D	249.28	581.80	142.82	26.84	145.02	0.985	Leading
E	249.28	592.20	145.45	27.03	147.62	0.985	Leading
A	239.22	621.00	147.10	26.66	148.60	0.990	Lagging
B	239.21	619.60	146.30	26.96	148.20	0.987	Lagging
C	239.24	622.80	147.20	26.92	149.00	0.988	Lagging
D	239.25	605.30	142.90	27.01	144.80	0.987	Lagging
E	239.24	616.40	145.60	26.63	147.50	0.987	Lagging
A	229.21	648.20	147.30	26.73	148.60	0.991	Lagging
B	229.17	646.40	146.50	26.85	148.10	0.989	Lagging
C	229.17	649.70	147.30	26.86	148.90	0.989	Lagging
D	229.17	631.20	143.00	26.87	144.70	0.989	Lagging
E	229.18	643.20	145.80	26.71	147.40	0.989	Lagging
A	219.15	677.70	147.40	27.18	148.50	0.992	Lagging
B	219.14	675.80	146.70	27.20	148.10	0.990	Lagging
C	219.13	679.60	147.50	27.12	148.90	0.991	Lagging
D	219.12	659.80	143.10	27.02	144.60	0.990	Lagging
E	219.13	672.40	145.90	27.20	147.30	0.990	Lagging
A	209.09	710.90	147.70	27.16	148.60	0.993	Lagging
B	209.06	708.00	146.80	27.22	148.00	0.992	Lagging
C	209.06	712.30	147.70	27.00	148.90	0.992	Lagging
D	209.06	691.30	143.30	27.41	144.50	0.992	Lagging
E	209.08	704.80	146.20	27.20	147.40	0.992	Lagging

Test Item Photographs

TI-15186


Images of Product(s) under test includes (where possible) labelling, Driver and Light engine details



Top View



Bottom View




Installed Driver



Installed LED Modules

Appendix 1: Test item set-up



----- END OF REPORT -----