

96630597 ESCORT LED I-SLCT 800/1000-840 OP WH

| | | | | | | | | |
|-------------------|------|------|--|--|--|--------|-------------------|--|
| LED 10W ESCT_1000 | IP65 | IK10 | | | | 850 °C | T _a 25 | |
|-------------------|------|------|--|--|--|--------|-------------------|--|

A durable, all weather bulkhead for surface mounting.

A self-contained, IP65, weatherproof bulkhead luminaire. Electronic, fixed output control gear. Durable, white, stove enamelled die-cast aluminium body and opal polycarbonate diffuser with vandal resistant screw fixings (Type T25 TORX screwdriver required). Suitable for interior and exterior industrial or public amenity usage. Lumen output selectable via internal switch. Complete with 4000K LED


Dimensions: 352 x 102 x 79 mm

Total power: 8 W


Weight: 1.2 kg



TLG_ESCT_F_LEDPDB.jpg



TLG_ESCT_M_LEDLD1.wmf



TLG_SP_0043323.ltd

Lamp position: 1000lm

Light Source: LED

Luminaire luminous flux*: 1000 lm

Luminaire efficacy*: 103 lm/W

Lamp efficacy: 103 lm/W

Colour Rendering Index min.: 80

LOR: 1,00 ULOR: 0,08 DLOR: 0,92

Correlated colour temperature*: 4000 Kelvin

Chromaticity tolerance (initial MacAdam)*: 3

Rated median useful life*:

50000h L70 at 25°C

Ballast: 1x HF_ Tridonic LC

Luminaire input power*: 9.7 W

Dimming: FO

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Colour temperature is subject to a tolerance of up to ± 150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG0 or RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

© Thorn Lighting